



KHV - 456s 5" Color LCD Monitor

- Hands-Free System
- communication
- Emergency
- Absence Function
- Door Release
- Telephone connection

KHV - 456s Function

- For Multiple Families, Villa & Apartment
- Hands-free System
- Communication
 - Monitor to Door Camera / Common Gate Camera (Audio & Video)
 - Monitor to Guard Office Interphone (Audio only)
 - Telephone
- Emergency Function
- Absence Function
- Door Release
- Embedment Type

KHV - 456 Specification

ITEM	Specification
Power	AC 110 ~ 220V, 56/60 Hz
Telephone line	Electronic / Mechanical combined use
Communication System	Hands-Free
Assurance temperature	0 ~ +50°C
TFT LCD Monitor	5" TFT LCD
Dimension	294(W) X 230(H) X 17(D)mm



KC-C50 – Outdoor camera

Wide view angle(120°)

Movable colour camera

Dimensions 95(W) X 127(H) X 46(D)mm

Item	Specification
MONITOR	KHV-454S(KHV-454SMT) / KTD-505
Power source	AC 110 or 220V
Power consumption	Max 15W / Max 8W
Telephone line	(Electronic / Mechanical combined use)
Communication system	Hands-free
Assurance temperature	0 ~ +50°
TFT LCD Monitor	5" TFT LCD
TV system	PAL or NTSC
Installation	Embedment type
Dimension	310(W) X 240(H) X 15(D)mm / 300(W) X 52(H) X 280(D)mm
DOOR CAMERA	KC-C50 / KLP-203R3S
Power source	DC 12V ±1V (Power from monitor) / DC 24V (Power supply)
Power consumption	Max 2.5W
Assurance temperature	-10 ~ 50°
Image sensors	1/3" CCD (270,000 / 320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,734KHz / Vertical 50Hz or 60Hz
Lens	F:2.0, f=3.0mm
Output Impedance	Picture : 75ohm, Voice : 600ohm
Minimum illumination	0.1 Lux (LED ON)
Angle of picture	Diagonal : 120°, angle adjustable
TV system	PAL or NTSC
Installation	Embedment type
Dimension	95(W) X 127(H) X 46(D)mm / 260(W) X 320(H) X 86(D)mm